



3600 SERIES - GRADE 2 TUBULAR

WARRANTY	Five-year warranty
FEATURES	<ul style="list-style-type: none"> Heavy duty residential - medium duty commercial No exposed mounting screws Non-handed Conventional cylinder or Small Format Interchangeable Core option available
Certifications:	<ul style="list-style-type: none"> BHMA Certified ANSI A156.2 Series 4000 Grade 2 ADA Compliant ANSI A117.1 Accessibility Code UL/cUL Listed for all functions up to 3 hours for "A" label single doors UL10C Positive Pressure Rated UL10B Neutral Pressure Rated
Lever Options:	Archer, August, Withnell levers
Options:	<ul style="list-style-type: none"> Tactile warning Split finish
SPECIFICATIONS	
Standard Door Prep:	<ul style="list-style-type: none"> 2-1/8" (54 mm) diameter (bore) Latch hole: 1" (25 mm) diameter (cross bore)
Exposed Trim:	<ul style="list-style-type: none"> Levers: Cast zinc Rose: Wrought brass
Rose Diameter:	2-15/16" (75 mm)
Lock Chassis:	Heavy gauge steel, zinc dichromated
Keys:	Two operating keys supplied per lock
Cylinders/Cores:	<ul style="list-style-type: none"> Brass - keyed different - Schlage C Keyway - Standard Cylinder drilled 6-pin, keyed 5-pin - Standard Other keying options, including keyed 6-pin, available from factory (see cylinder, core and keying section) Zero bit cylinders will be 6 pin keyed - standard Small Format Interchangeable Core option available SFIC uncombined or combined, brass 6- or 7-pin cores sold separately
Door Thickness:	1-3/8" - 1-3/4" (35 mm - 45 mm)
Backset:	<ul style="list-style-type: none"> Adjustable 2-3/8" - 2-3/4" (60 mm - 70 mm) Preset at factory for 2-3/8" (60 mm)
Latchbolt:	<ul style="list-style-type: none"> 1/2" (13 mm) throw, stainless steel 1" x 2-1/4" (25 mm x 57 mm) faceplate Square corner faceplate standard, round corner available Deadlocking latchbolt prevents manipulation when door is closed; keyed functions only
Strike:	3935 ASA 1-1/4" x 4-7/8" (32 mm x 124 mm) strike - Standard
Functions:	10 Passage, 17 Dummy, 40 Privacy, 53 Entry, 70 Classroom, 80 Storeroom
FINISHES	US3, US4, US10, US10B, US26, US26D