

Auxiliary Deadlock

- 1 Confirm lockset is the correct bevel for the door. If not, loosen the screws fastening front to case. Rotate front to proper bevel and retighten screws.
- 2 Prepare door and frame using template T31180.
- 3 Mount lock using two combination screws.
- 4 Place cylinder thru cylinder collar and screw into lock. (See Figure 1)

NOTES:

- Pull key slightly out of cylinder to help thread into lockbody.
- Cylinder must be oriented correctly. (See Figure 2)




Figure 2




Figure 1

- 5 Tighten appropriate set screw into cylinder.

- 6 Attach turn-piece as shown. (See Figure 3)

For 4122 function, turn-piece must be inverted. (See Figure 4)
For ergonomic turn-piece, see alternative instructions on page two.




Figure 4




Figure 3

- 7 Attach outside front using two 1/4" machine screws. (See Figure 1)

- 8 Install strike and strike box (optional) using two combination screws. (See Figure 5)

INSIDE FACE OF DOOR




Figure 5



The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Corbin Russwin[®]

ASSA ABLOY

Ergonomic Turn-Piece

1. After installing the lockbody, insert the alignment tool.
2. Place back plate over the alignment tool and use a carpenter's square to orient. (See Figure 6)
3. Mark three screw holes and remove backplate, alignment tool, cylinder (if applicable) and lockbody.
4. Drill two pilot holes for #6 screws (Wood = 3/32" holes, Metal = Drill/Tap for #6-32 machine screws).
5. Drill 3/16" clearance hole, 1/16" deep for upper mounting screw.
6. Re-install lockbody and cylinder. (See steps 3-5 on page 1)
7. Install back plate using two #6 mounting screws. (See Figure 6)
8. Install turn-piece using one #6 machine screw. (See Figure 7)



⚠️ WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

For installation assistance contact Corbin Russwin
1-800-543-3658 • techsupport.corbinrusswin@assabloy.com

Corbin Russwin, Inc.
225 Episcopal Road
Berlin, CT 06037 USA
Phone: 800-543-3558
Fax: 800-447-6714
www.corbinrusswin.com

Corbin Russwin is a brand associated with ASSA ABLOY Access and Egress Hardware Group, Inc., an ASSA ABLOY Group company. Copyright © 2011, 2020, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.