



## 3400 SERIES - GRADE 1 CYLINDRICAL - HEAVY DUTY

<b>WARRANTY</b>	Lifetime warranty
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>Heavy duty commercial, industrial, institutional</li> <li>No exposed mounting screws</li> <li>Non-handed</li> <li>Conventional cylinder, Small Format Interchangeable Core, and Large Format Interchangeable Core option available</li> </ul>
Certifications:	<ul style="list-style-type: none"> <li>BHMA Certified ANSI A156.2 Series 4000 Grade 1</li> <li>ADA Compliant ANSI A117.1 Accessibility Code (levers only)</li> <li>ANSI A250.13 Severe Windstorm Resistant Component</li> <li>UL/cUL Listed for all functions up to 3 hours for "A" label doors</li> <li>UL10C Positive Pressure Rated</li> <li>UL10B Neutral Pressure Rated</li> </ul>
Lever Options:	Apollo knob; Archer, August, Withnell levers
Options:	<ul style="list-style-type: none"> <li>Lead lined (leversets only)</li> <li>Tactile warning (levers only)</li> <li>Antimicrobial coating (26D finish only)</li> <li>Split finish</li> <li>Additional latchbolts and strikes available</li> </ul>
<b>SPECIFICATIONS</b>	
Standard Door Prep:	<ul style="list-style-type: none"> <li>2-1/8" (54 mm) diameter (bore)</li> <li>Latch hole: 1" (25 mm) diameter (cross bore)</li> </ul>
Exposed Trim:	<ul style="list-style-type: none"> <li>Knobs: Wrought brass or stainless steel</li> <li>Levers: Cast zinc</li> <li>Rose: Wrought brass or stainless steel</li> </ul>
Rose Diameter:	3-17/32" (90 mm) levers; 3" (76 mm) knobs
Lock Chassis:	<ul style="list-style-type: none"> <li>Heavy gauge steel, zinc dichromated for corrosion resistance</li> <li>Free wheeling (levers only)</li> <li>Thru-bolt mounting (levers only)</li> </ul>
Keys:	Two operating keys supplied per lock
Cylinders/Cores:	<ul style="list-style-type: none"> <li>Brass 6-pin, keyed different - Schlage C Keyway - Standard</li> <li>Cylinder drilled 6-pin, Keyed 5-pin - Standard</li> <li>Other keying options, including keyed 6-pin, available from factory (see cylinder, core and keying section)</li> <li>Zero bit cylinders will be 6 pin keyed - standard</li> <li>Small Format Interchangeable Core option available</li> <li>SFIC uncombined or combined, brass 6- or 7-pin cores sold separately</li> <li>Large Format Interchangeable Core option available - leversets only</li> <li>LFIC zero bitted or combined, brass 6-pin cores sold separately - Schlage C only</li> </ul>
Door Thickness:	<ul style="list-style-type: none"> <li>Knobs: 1-3/8" - 1-3/4" (35 mm - 45 mm)</li> <li>Levers: 1-3/8" - 2" (35 mm - 51 mm)</li> </ul>
Backset:	<ul style="list-style-type: none"> <li>2-3/4" (70 mm) - Standard</li> <li>2-3/8" (60 mm) - Optional</li> <li>3-3/4" (94 mm) - Optional</li> <li>5" (128 mm) - Optional</li> </ul>
Latchbolt:	<ul style="list-style-type: none"> <li>1/2" (13 mm) throw, stainless steel</li> <li>1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate</li> <li>Square corner faceplates standard, round corner available</li> <li>Deadlocking latchbolt prevents manipulation when door is closed; keyed functions only</li> <li>3/4" (18 mm) latch available</li> </ul>
Strike:	3935 ASA 1-1/4" x 4-7/8" (32 mm x 124 mm) strike - Standard
Functions:	10 Passage, 17 Dummy, 40 Privacy, 50 Entry/Office, 53 Entry, 70 Classroom, 73 Corridor (levers only), 80 Storeroom, 95 Intruder Classroom (levers only)
<b>FINISHES</b>	<ul style="list-style-type: none"> <li>US3, US4, US10, US10B, US26, US26D (levers only)</li> <li>US3, US32D (knobs only)</li> </ul>