

## BB1173

Five Knuckle  
 - Ball Bearing -  
 Standard Weight



### PRODUCT SPECIFICATIONS

#### DESCRIPTION:

- ANSI A8412
- Two ball bearings
- Non-rising removable pin with button tip and plug
- Beveled surface leaf
- Reversible
- Thru-bolts and grommets for wood door applications
- For use on regular weight hollow metal or wood composite doors with hollow metal frames requiring medium frequency service

#### FINISHES:

- USP, US10, US10A, US10B, US26D

#### NOTES:

- 4" is for 1-3/8" door. 4" for 1-3/4" door is available by consulting the Hager Tech Department

### PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	DOOR LEAF SCREW SIZE (MACHINE)	JAMB LEAF SCREW SIZE (WOOD)
4*	102	0.129	7	2 x 1/4 - 20 OH	1/2 x 12 - 24 FH
4 1/2	114	0.134	7	2 x 1/4 - 20 OH	1/2 x 12 - 24 FH
5	127	0.145	8	1/2 x 12 - 20 FH	

\* for 1-3/8" doors

HINGE SIZE (INCHES)	HINGE SIZE (MM)	DOOR LEAF WIDTH (INCHES)	DOOR LEAF WIDTH (MM)	JAMB LEAF "A" (INCHES)	JAMB LEAF "A" (MM)	JAMB LEAF "B" (INCHES)	JAMB LEAF "B" (MM)	JAMB LEAF "C" (INCHES)	JAMB LEAF "C" (MM)	JAMB LEAF "D" (INCHES)	JAMB LEAF "D" (MM)
4*	102	2 5/16	59	113/16	46	1/2	13	15/16	33		
4 1/2	114	2 9/16	65	2	51	1/2	12.5	11/2	38		
5	127	2 7/8	73	2	51	1/2	12.5	11/2	38		

\* for 1-3/8" doors