



3400 SERIES - ELECTRIFIED - GRADE 1 CYLINDRICAL HEAVY DUTY

WARRANTY

- Lifetime warranty on mechanical locking components
- One-year warranty on electric components

FEATURES

- Deadlocking latchbolt
- Key override allows latchbolt to be momentarily retracted with the key even though electrically locked. Note that locks that are electrically unlocked may not be locked via the key cylinder.
- Inside lever always allows egress
- Interface with life-safety systems
- Continuous-duty solenoids



Function:

80 - Storeroom

Applications:

- Provides remote locking and unlocking ideal for access control where added security is necessary
- Stairtower doors
- Office doors
- Classrooms
- Elevator lobby doors
- Computer rooms
- Hospital equipment rooms
- Pharmaceutical storage rooms

Voltage:

- 12V AC/DC; current - .250AMP
- 24V AC/DC; current - .150AMP
- Specify 12V or 24V when ordering

FINISHES

US3, US4, US10, US10B, US26, US26D

Function	Function No.	Function Description
Storeroom - Fail Safe	3480EL	Outside lever continuously locked electrically. Latchbolt operable from the outside by key, by breaking electric current, or by power failure. Auxiliary latch deadlocks latchbolt when door is closed. Inside always free for immediate egress.
Storeroom - Fail Secure	3480EU	Outside lever continuously locked. Latchbolt operable from the outside by key or by applying electrical current. Auxiliary latch deadlocks latchbolt when door is closed. Inside always free for immediate egress.
Storeroom - Request to Exit	3480RX	Monitors inside lever rotation. Incorporates into fire alarm system or in conjunction with an electromagnet.
Storeroom - Fail Safe w/ Request to Exit	3480ELRX	Outside lever continuously locked electrically. Latchbolt operable from the outside by key, by breaking electric current, or by power failure. Auxiliary latch deadlocks latchbolt when door is closed. Inside always free for immediate egress. Inside lever rotation is monitored. Incorporates into fire alarm system.
Storeroom - Fail Secure w/ Request to Exit	3480EURX	Outside lever continuously locked. Latchbolt operable from the outside by key or by applying electrical current. Auxiliary latch deadlocks latchbolt when door is closed. Inside always free for immediate egress. Inside lever rotation is monitored. Incorporates into fire alarm system.

