

**Cylinder**

**4111(6)-3071**  
Cast Iron Cylinder Assembly

- Handed
- Standard

**Covers**

**4110-72**  
Plastic Cover

- Non-handed
- Standard



**4110-72MC**  
Metal Cover

- Handed
- Required for plated finishes and custom powder coat finishes
- Optional

*Left hand shown*

**Arms**

**4110-3049EDA**  
Hold-Open Arm

- Handed
- Optional
- Provides hold-open function, adjustable at shoe



**4110-3049FL**  
Fusible Link Arm

- Handed
- Releases hold-open function adjustable at shoe when exposed to temperatures above 165° F
- Optional



**4110-3077CNS**  
Cush-N-Stop Arm

- Non-handed
- Features solid forged steel main arm and forearm with built-in stop in soffit shoe

*NOTE: Check local codes before specifying FL arms. NOT A life safety product!*



**4110-3077EDA**  
Extra Duty Arm

- Non-handed
- Features forged, solid steel main and forearm for potentially abusive installations



**4110-3077EDA/ 62G**  
Extra Duty Arm

- Non-handed
- Features forged, solid steel main and forearm for potentially abusive installations
- Optional 4110-62G thick hub shoe for blade stop clearance

**Arms**

**4110-3049CNS**  
HCUSH Arm

- Non-handed
- Provides hold-open function with templated stop/ hold-open points.
- Handle controls hold-open function



**4110-3077SCNS**  
Spring CUSH Arm

- Non-handed
- For abusive applications features solid forged steel main arm and forearm with spring loaded stop in the soffit shoe
- Optional



**4110-3049SCNS**  
Spring HCUSH Arm

- Non-handed
- For abusive applications features solid forged steel main arm and forearm with spring loaded stop in the soffit shoe
- Handle controls hold-open function
- Optional

**Installation Accessories**

**4110-18**  
Plate

- Required for push side mount where top rail is less than 5-1/8" (130 mm), measured from the stop
- Requires minimum 2" (51 mm) minimum top rail



**4110-30**  
CUSH Shoe Support

- Provides anchorage for fifth screw used with CUSH arm, where reveal is less than 3-1/16" (78 mm)



**4110-61**  
Blade Stop Spacer

- Lowers parallel arm shoe to clear 1/2" (13 mm) blade stop



**4110-419**  
PA Flush Panel Adapter

- Provides horizontal mounting surface for CUSH shoe on single rabbed or flush frame