

DCH1000 Series

Heavy duty surface door closers



Specifications

- Grade 1 compliant, UL 10C Listed (non-hold open arms), ADA compliant at size 1
- Adjustable spring size 1-6
- 6 3/4" x 2 3/8" mounting hole pattern
- Staked, independent adjustment values: sweep speed, latch speed, and back-check
- Single piece, cast aluminum body
- Universal hardware pack

Closers

Product description	Cylinder type	Cover	Arm function	Finish
DCH1000-STD-FULL-RW/PA-ALUM	STD	Full	Rw/PA	ALUM
DCH1000-STD-FULL-RW/PA-DKBRZ	STD	Full	Rw/PA	DKBRZ
DCH1000-STD-FULL-HW/PA-ALUM	STD	Full	Hw/PA	ALUM
DCH1000-STD-FULL-DS-ALUM	STD	Full	DS	ALUM
DCH1000-STD-FULL-DS/HO-ALUM	STD	Full	DS/HO	ALUM

Arm types

Regular arm (Rw/PA): Non-handed, regular arm with adjustable forearm assembly to accommodate a range of doors and frame reveal conditions. Mounts hinge side, top jamb or parallel arm. PA shoe included to allow installation in a parallel arm configuration.

Hold-open arm (Hw/PA): Non-handed, hold open arm with adjustable forearm assembly to accommodate a range of doors and frame reveal conditions. Mounts hinge side, top jamb or parallel arm. PA shoe included to allow installation in a parallel arm configuration.


Dead stop arm (DS): Non-handed, stamped, heavy duty, parallel arm includes a positive mechanical stop and non-adjustable forearm assembly for high volume traffic or potentially abusive installation conditions.

Dead stop hold-open arm (DS/HO): Non-handed, stamped, heavy duty, hold-open parallel arm includes a positive mechanical stop and non-adjustable forearm assembly for high volume traffic or potentially abusive installation conditions. Also includes a manually selective hold open function.

Finishes



ALUM/689



DKBRZ/695