



The 9140 BENCHMARK by LCN is an electrically powered low-energy operator. It provides easy access for people with disabilities, or the elderly. Designed primarily for automatic opening applications that occasionally require manual opening. The BENCHMARK is a cost-effective solution for retrofitting an activated or manual door.

Certifications	Grade 1 - ANSI A156.19, UL325/228, ADA, 100 Hour Salt Spray, Meets BAA - Buy American Act	Fasteners	Wood and machine screws
Handing	Non-Handed	Mounting	Single interior door, surface mount, offset pivot / butt hinge (Push Side)
Door Width	<ul style="list-style-type: none"> ■ 26" - 48" ■ 26" minimum door width for 27" ■ 36" door width only for full length pull operator 	Arms	Regular arm
Warranty	2 years	Finishes/Colors/ Powder Coat	<ul style="list-style-type: none"> ■ Anodized aluminum, standard ■ Dark bronze, optional

Special Templates

Customized installation templates or products may be available to solve unusual applications. Contact LCN Product Support for assistance.

MOUNTING						HANDING		FINISH	COVER	ARM FUNCTION			
●	○	○	○	○	○	○	●	○	●	○	○	○	
SURFACE MOUNT SINGLE DOOR						STANDARD ANODIZED			STANDARD (SINGLE LEVER)		REGULAR (DOUBLE LEVER)		
SURFACE MOUNT SIMULTANEOUS PAIR						METAL			DOUBLE EGRESS (PUSH/PULL)		OFFSET PIVOT BUTT HINGE ARM		
SURFACE MOUNT INDEPENDENT PAIR									CENTER PIVOT ARM				
CONCEALED SINGLE DOOR													
CONCEALED SIMULTANEOUS PAIR													
CONCEALED INDEPENDENT PAIR													
HANDED						NON-HANDED							

● AVAILABLE

○ NOT AVAILABLE

● AVAILABLE
○ NOT AVAILABLE