



9400 Series

Surface Mounted Electric Strike

Works with rim exit devices with a 1/2" throw latchbolt

Stylish Looks

Slim-Line Profile

Unique 1/2" slim-line form
Decorative cover for a sleek look
Available in 7 finishes to match any decor

Convenient

Easy Installation

Completely surface mounted for quick installation
Installs in metal or wood frames
Simple fail secure/fail safe and 12/24VDC conversions

Quality

Reliable Strength

Exceeds Grade 1 standards for strength and performance
UL 1034 burglary-resistant listed
Components encased in 1/2" stainless steel housing

Model 9400

The Easy
Install,
Slim-Line,
Surface
Mounted
Solution

ASSA ABLOY, the global leader in door opening solutions

hesinnovations.com



RIM EXIT DEVICES



FIELD SELECTABLE
(12 OR 24VDC)



FIELD SELECTABLE
(FAIL SECURE/FAIL SAFE)



GRADE 1



OUTDOOR RATED



UL 1034
BURGLARY LISTED



9400 Series

Surface Mounted Electric Strike

Features

Standard Features

- Installs in metal or wood frames
- Decorative cover for a sleek look
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

Optional Features

- LBM** » Latchbolt monitor
- LBSM** » Latchbolt strike monitor

Accessories

- 9400/9500/9600-108** » Spacer plate (black or 630 finish)
- 9000-MTK** » Metal template kit
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 613E** » Dark oxidized satin bronze (NEW)
- 629** » Bright stainless steel

Specifications

Listings and Patents

- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (6th edition) listed
- ANSI/BHMA A156.31, Grade 1
- RoHS compliant
- Patents: 6,390,520; 8,454,036
- Patent Pending

Frame Application

- Metal
- Wood

Electrical (continuous duty)

- .45 Amps @ 12VDC
- .25 Amps @ 24VDC
- PoE friendly

