

**Cylinder**



**4040SE-3071**  
Cylinder Assembly

- Non-handed
- Cast iron
- Standard

**Covers**



**4040SE-72**  
Plastic Cover

- Non-handed
- Clip-on
- Standard



**4040SE-72MC**  
Metal Cover

- Handed
- Required for plated finishes and custom powder coat finishes
- Optional

**Arms**



**4040SE-3077**  
Standard Arm

- Non-handed
- Adjustable to select hold-open point



**4040SE-3077DE**  
Double Egress Arm

- Handed
- For pull side installations on double egress doors and frames
- Not required for push side mounting on double egress frames
- Optional

**Tracks**




**4040SE-3038**  
SE Track

- Non-handed
- For SE closers. Mounts on either head frame or stop
- 24V or 120V AC/DC input for holding solenoid, please specify.
- Includes test switch assembly with fuse
- Standard



**4040SEL-3038**  
SEL Long Track

- Non-handed
- Mounts on either head frame or stop
- 24V or 120V AC/DC input standard for holding solenoid, please specify
- Includes test switch assembly with fuse
- Optional

**Switch****4040SE-3436**  
Test Switch**Installation Accessories****4040SE-18**  
Plate

- Required where top rail is less than 3-1/2" (89 mm)
- Requires minimum 2" (51 mm) top rail
- Installations require a SPECIAL TEMPLATE

**4040SE-18PA**  
Plate


- Required where top rail is less than 5-3/4" (146 mm)
- Requires minimum 2" (51 mm) top rail
- Installations require a SPECIAL TEMPLATE

**4040SE-81**  
Conduit Quick-Connector

- Two piece connector for use with 1/2" conduit

**4040SE-3034SE**  
Track Roller & Track Slider

- Quiet, low friction roller assembly
- Shoulder dimension "X" = 1/8" (3 mm)
- Alloy metal slider for use in SE series tracks only

**4040SE-3210**  
Transformer

- Reduces line voltage from 120V to 24V AC
- Mounted on cover for 4" (102 mm) x 4" x 2-1/8" (54 mm) junction box (by others)