



## 4500 SERIES - ACCESSORIES

### 4926

#### Cylinder Dogging Conversion Kit

For use with panic-rated 4500 Series devices

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK. Anti-microbial available with US26D, US32D.

Packaging: One (1) each dogging plate, cylinder collar, cash box nut

Notes: • Mortise cylinder 3902 with standard cam, sold separately  
• Specify 36" (914 mm) or 48" (1219 mm)

### 4927

#### Bottom Latch Assembly

For use with 4500 Series Surface Vertical Rod exit device

Description: 1/2" (13 mm) throw, pullman type, held retracted during door swing, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK

Packaging: One (1) bottom latch with cover and appropriate fasteners

### 4928

#### Top Latch Assembly

For use with 4500 Series Surface Vertical Rod exit device

Description: 1/2" (13 mm) throw, pullman type, held retracted during door swing, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK

Packaging: One (1) top latch with cover and appropriate fasteners

### 2-649-0250/2-649-0257

#### Photoluminescent

Push bar cover option for 4500 & 4600 Series exit devices

Description: 2-649-0250 - 4500/4600 36"  
2-649-0275 - 4500/4600 48"

Features: • Requires no wiring or maintenance  
• Recharges with exposure to ambient light

### 4929

#### Top/Bottom Rod Replacement Kit

For use with 4500 Series Surface Vertical Rod exit device

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK.

Packaging: One (1) each 45-1/4" (1149 mm) rod, rod guide, rod connector, and appropriate fasteners

### 4929C

#### Concealed Rod Replacement Kit

For use with 4500 Series Concealed Vertical Rod exit device

Material: Hardened aluminum

Finishes: US26D

Packaging: One (1) each 46-5/8" (1184 mm) rod, rod connector and appropriate fasteners

### 4930R

#### Shim Kit

For use with 4500 Series Rim exit devices where a glass bead kit would interfere with exit device

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK

Packaging: Two (2) each 1/8" (3 mm) shims and appropriate fasteners

### 4930S

#### Shim Kit

For use with 4500 Series Surface Vertical Rod exit devices where a glass bead kit would interfere with exit device

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK

Packaging: Two (2) each 1/8" (3 mm) shims and appropriate fasteners



## 4500 SERIES - ACCESSORIES



### 4932C

#### Head Cover

For use with 4500 Series Concealed Vertical Rod or Mortise exit devices

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK. Anti-microbial available with US26D, US32D.  
Packaging: One (1) head cover and four (4) each M4 x 6mm MS



### 4932R

#### Head Cover

For use with 4500 Series Rim exit device

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK, Anti-microbial available with US26D, US32D.  
Packaging: One (1) head cover and four (4) each M4 x 6mm MS



### 4932S

#### Head Cover

For use with 4500 Series Surface Vertical Rod exit devices

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK. Anti-microbial available with US26D, US32D.  
Packaging: One (1) head cover and four (4) each M4 x 6mm MS



### 4936

#### 24" Extension Rod Kit

For use with 4500 Series Vertical Rod exit devices

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK  
Packaging: One (1) each 24" (610 mm) extension rod, rod connector, rod guide, plus wood and machine screws  
Notes: Extension rods threaded on both ends; if cuts are required, cut the standard rod on non-threaded end



### 4937

#### 36" Extension Rod Kit

For use with 4500 Series Vertical Rod exit devices

Finishes: US3, US4, US10, US10B, US26, US26D, US32D, BLK  
Packaging: One (1) each 36" (914 mm) extension rod, rod connector, rod guide, plus wood and machine screws  
Notes: Extension rod threaded on both ends; if cuts are required, cut the standard rod on non-threaded end



Standard



Flush

### END CAPS

For use with all 4500 and 4600 Series exit devices

Finishes: Anti-microbial available with US26D, US32D.

#### Standard      Flush

US3	(2-649-0038)	(2-649-0218)
US4	(2-649-0039)	(2-649-0220)
US10	(2-649-0040)	(2-649-0214)
US10B	(2-649-0041)	(2-649-0215)
US26	(2-649-0042)	(2-649-0216)
US26D	(2-649-0043)	(2-649-0217)
US32D	(2-649-0044)	(2-649-0219)
BLK	(2-649-5013)	(2-649-5012)

Packaging: One (1) each cap and bracket plus fasteners



### 2-649-0166

#### Fire Bolt Kit

For use with fire-rated 4500 Series Vertical Rod less bottom rod device

Faceplate: 1-25/32" x 1" (45 mm x 25 mm)  
Bolt Diameter: 7/16" (11 mm)  
Bolt Length: 1-1/2" (38 mm)  
Materials: Stainless steel  
Packaging: One (1) each fire bolt, plastic plug, head cover plug, and appropriate fasteners  
Notes: Required with a fire-rated pair of LBR or LLB devices to ensure rating