



The 1250 Series cast aluminum closer is designed for low-frequency and low abusive traffic areas. This cast aluminum closer is ideal for aluminum storefronts, interior offices and many other applications. Combining dependable operation, low maintenance and a patented stylish look - with or without the optional slim line cover. And with the most common hole pattern in the industry, the 1250 Series is the perfect choice for easy aftermarket replacement.

Certifications	Grade 1 - ANSI A156.4, UL 10C, ADA, 100 Hour Salt Spray, Meets BAA - Buy American Act
Body Construction	<ul style="list-style-type: none"> ■ Cast Aluminum Body ■ Full Complement Bearing ■ 1-3/8" Diameter Piston ■ 5/8" Diameter Single Heat Treated Pinion Journal
Fluid	All Weather Fluid
Handing	Non-Handed
Templating	Peel-n-Stick templates - 3/4" x 9-1/16" Mounting Hole Pattern
Size	Adjustable Spring Size 1-5
Warranty	15 years

Cover	<ul style="list-style-type: none"> ■ Slim Line Cover, Optional
Fasteners	Universal Screw Pack (UNIV)
Mounting	Hinge (Pull Side), Top Jamb (Push Side), Parallel Arm (Push Side)
Arms	Tripack includes Regular, Top Jamb, and Parallel Arm (Rw/PA)
Finishes/Colors/ Powder Coat	<ul style="list-style-type: none"> ■ Aluminum (689) ■ Statuary Bronze (690) ■ Light Bronze (691) ■ Black (693) ■ Dark Bronze (695) ■ Brass (696) ■ Custom colors optional
	<ul style="list-style-type: none"> ■ Optional SRI primer - powder coat only

Special Templates

Customized installation templates or products may be available to solve unusual applications. Contact LCN Product Support for assistance.

MOUNTING	FINISH	COVER	CYLINDER	*ARM FUNCTION
HINGE (PULL SIDE) TOP JAMB (PULL) TOP JAMB (PUSH) PARALLEL ARM STOP FACE	PAINT POWDER COAT PLATED	PLASTIC METAL	NON-HANDED NON-SIZED ACCESSIBILITY DELAYED ACTION	180° 180° 180° 110° 110°

● AVAILABLE
○ NOT AVAILABLE

● Closer available with less than 5.0 lbs. opening force on 36" door.
* Maximum opening/hold-open point with standard template.