

Cylinders**4020(6)-3071**
Cast Iron Cylinder Assembly

- Handed
- Standard

Covers**4020-72**
Plastic Cover

- Handed
- Standard

**4020-72MC**
Metal Cover

- Handed
- Required for plated finishes and custom powder coat finishes
- Optional

Arms**4020-3077**
Regular Arm

- Non-handed

**4020-3077L**
Long Arm

- Non-handed
- Includes 4020-79LR for deep reveals, (see page 14 for allowable reveals)
- Optional

**4020-3049**
Hold-Open

- Handed
- Provides hold-open function, adjustable at elbow
- 5-3/4" (146 mm) maximum reveal, 140° hold open
- Optional

**4020-3049FL**
Fusible Link

- Handed
- Releases hold-open function, adjustable at shoe, when exposed to temperatures above 165° F
- 3-7/8" (98 mm) maximum reveal
- Optional

NOTE: Check local codes before specifying FL arms. NOT A life safety product!

Installation Accessories**4020-18**
Plate

- Required where head frame is less than 3-7/16" (87 mm)
- Requires minimum 1-3/4" (44 mm) minimum head frame and 2-3/4" (70 mm) top rail
- 3-7/8" (98 mm) maximum reveal

**4020-18G**
Plate

- For flush ceiling condition
- Requires minimum 1-3/4" (44 mm) minimum head frame and 2-3/4" (70 mm) top rail