


The 4040XP is LCN's most durable and flexible heavy duty closer designed for institutional and other demanding high traffic applications.

| Certifications | Grade 1 - ANSI A156.4, UL 10C, ADA, 100 Hour Salt Spray, Meets BAA - Buy American Act |
|-------------------|--|
| Body Construction | Cast Iron Body Full Complement Bearings 1-1/2" Diameter Piston 3/4" Diameter Double Heat Treated Pinion Journal |
| Fluid | All Weather Liquid X Fluid |
| Handing | Non-Handed |
| Templating | Peel-n-Stick templates - 2-1/4″ x 5″ Mounting Hole Pattern |
| Size | Adjustable Spring Size 1-6, includes Patented Green Dial |
| Warranty | 30 years |

| Cover | Plastic, StandardMetal, Optional |
|---------------------------------|--|
| Fasteners | Self Reaming and Tapping Screws (SRT) |
| Mounting | Hinge (Pull Side), Top Jamb (Push Side), Parallel Arm (Push Side) |
| Arms | Regular Arm |
| Finishes/Colors/ Powder Coat | Aluminum (689) Statuary Bronze (690) Light Bronze (691) Black (693) Dark Bronze (695) Brass (696) Custom colors optional |
| | Optional SRI primer - powder coat onlyOptional plated finishes |

Special Templates

Customized installation templates or products may be available to solve unusual applications. Contact LCN Product Support for assistance.



- AVAILABLENOT AVAILABLE
- & Closer available with less than 5.0 lbs. opening force on 36" door.
- * Maximum opening/hold-open point with standard template.
- ** Advanced Variable Backcheck.
- *** Delay feature incorporates standard 4040 cylinder (not XP).

