

**Cylinder****3130SE-3071**  
SE Cylinder Assembly

- Handed
- Cast iron
- For various applications see "Table of Sizes" on 3130SE Series page 16
- Standard

**Arms****3130SE-3077T**  
Standard Arm

- Handed
- Adjustable to select hold-open point
- Standard

**3130SEL-3077T**  
Long Arm

- Handed
- Provides hold-open point from 110° to 130°, determined by track templating
- Used with SEL TRACK 3130SEL-3038 only
- Optional

**Tracks****3130SE-3038**  
SE Track

- Non-handed
- Circuitry accepts either AC or DC input
- 24V holding solenoid (24) or 120V holding solenoid (120), please specify
- Standard

**3130SEL-3038**  
SEL Long Track


- Non-handed
- Used with LONG ARM, 3130SEL-3077T, only
- Provides hold open point from 110° to 130°, determined by templating. Circuitry accepts either AC or DC input
- 24V holding solenoid (24) or 120V holding solenoid (120), please specify
- Optional

**Installation Accessories****3130SE-81**  
Conduit Quick-Connector


- Two piece connector for use with 1/2" conduit
- See page 21 for illustration

**3130SE-3034SE**  
Track Roller & Track Slider

- Quiet, low friction roller assembly
- Shoulder dimension "X" = 1/8" (3 mm)
- Alloy metal slider for use in SE series tracks only

**4040SE-3210**  
Transformer

- Reduces line voltage from 120V to 24V AC
- Mounted on plate for 4" (102 mm) x 4" x 2-1/8" (54 mm) junction box (by others)

**Switch****3130SE-3436**  
Test Switch