

### Cylinders



**4021(6)-3071**  
Cast Iron Cylinder Assembly

- Handed
- Standard

### Covers



*Left Hand Shown*

**4020-72**  
Plastic Cover

- Handed
- Standard



*Right Hand Shown*

**4020-72MC**  
Metal Cover

- Handed
- Required for plated finishes and custom powder coat finishes
- Optional

### Arms



**4020-3077**  
Regular Arm

- Non-handed



**4020-3077L**  
Long Arm

- Non-handed
- Includes 4020-79LR for deep reveals. (see page 14 for allowable reveals)
- Optional



**4020-3049**  
Hold-Open

- Handed
- Provides hold-open function, adjustable at elbow
- 5-3/4" (146 mm) maximum reveal, 140° hold open
- Optional



**4020-3049FL**  
Fusible Link

- Handed
- Releases hold-open function, adjustable at shoe, when exposed to temperatures above 165° F
- 3-7/8" (98 mm) maximum reveal
- Optional

*NOTE: Check local codes before specifying FL arms. NOT A life safety product!*

### Installation Accessories



**4020-18**  
Plate

- Required where head frame is less than 3-7/16" (87 mm)
- Requires minimum 1-3/4" (44 mm) minimum head frame and 2" (51 mm) top rail
- 3-7/8" (98 mm) maximum reveal



**4020-18G**  
Plate

- For flush ceiling condition
- Requires minimum 1-3/4" (44 mm) minimum head frame and 2-3/4" (70 mm) top rail