

Cylinder



4310ME-3971
ME Cylinder Assembly

- Handed
- Cast iron
- Specify 24V or 120V
- Standard



4310ME-3071
ME Cylinder/Plate Assembly

- Handed
- "On/Off" switch assembly controls hold-open function
- Circuitry accepts either AC or DC input
- 24V or 120V, please specify
- Standard

Cover



4310ME-72MC
Metal Cover

- Handed
- Standard

Arms



4310ME-3077SF
Swing-Free Arm

- Handed
- After door is placed in hold-open, secondary pivot point allows up to 160° swing without door closer resistance



4310ME-3077DE
Double Egress Arm

- Handed
- For double egress doors and frames
- 2-11/16" (68 mm) maximum reveal
- Optional

Track




4310ME-3038
Track

- Non-handed
- Standard

Switch

24V shown




4310ME-3351 Switch Assembly

- Provides continuous hold-open function
- 24V or 120V, please specify



4310ME-3034 Track Roller

- Quiet, low friction roller assembly
- Shoulder dimension "X" = 1/8" (3mm)



4310-3210 Transformer

- Reduces line voltage from 120V to 24V AC
- Mounted on cover for 4" (102 mm) x 4" x 2-1/8" (54mm) junction box (by others)



4310ME-3354 ME Wiring Harness

- Three wire harness with 6" (152 mm) leads for field wiring connections