25 Series
Types and functions

This page shows all 25 Series device and trim functions.

Functions (ANSI)	Rim device ANSI type 1 (F)–25-R	Vertical rod device ANSI type 2 (F)–25-V	Mortise lock device ANSI type 3 (F)–25-M	Concealed vertical rod device ANSI type 8 (F)–25-C
EO (01) Exit only, no trim.	25-R-EO	25-V-EO	25-M-EO	25-C-EO
DT (02) Entrance by trim when actuating bar is locked down.	25-R-DT	25-V-DT	25-M-DT	25-C-DT
NL (03) Entrance by trim when latchbolt is retracted by key. Key removable only when locked.	25-R-NL	25-V-NL	25-M-NL	25-C-NL
TP (05) Entrance by thumbpiece. Key locks or unlocks thumbpiece.	25-R-TP	25-V-TP	25-M-TP	25-C-TP
L or K (08) Entrance by knob or lever. Key locks or unlocks knob.	25-R-L/K	25-V-L/K	25-M-L/K	25-C-L/K
L(NL) or K(NL) (03) Entrance by knob or lever when latchbolt is retracted by key. Lever/knob is rigid. Key removable only when locked.	25-R-L/K(NL)	25-V-L/K(NL)	25-M-L/K(NL)	25-C-L/K(NL)