

Cylinders



4631-3971
Cast Iron Cylinder Assembly

- Non-handed
- Standard



4631-3071
Cast Iron Cylinder Assembly

- Non-handed
- Mounting plate
- Includes 4630-3454 Motor Clutch, 4630-3180 I/O Board Assembly and 4630-3462 Controller
- Standard



4631-3071CS
Cast Iron Cylinder Assembly

- Non-handed
- Mounting plate
- Includes 4630-3454 Motor Clutch, 4630-3180 I/O Board Assembly and 4630-3462 Controller
- Same as a 4630-3071 assembly except on/ off switch is concealed in endcap and no hold open switch is included (Separate key switches suggested)
- Standard

Cover



4630-72MC
Metal Cover

- Non-handed
- Standard

Track



4630-3038
Standard Track

- Non-handed
- Will not accept hold open clip or bumper assembly
- Standard

Arm



4630-3077T
Standard Arm

- Non-handed
- Track roller not included with arm

Installation Accessories



4630-3034
Track Roller


- Quiet low friction roller assembly
- Shoulder dimension "X" = 1/8" (3mm)

Installation Accessories



4630-334
Switch End Cap

- End cap (black powder coat finish only) with cut outs for installing on/off and hold open switches




4630-334-2
Blank End Cap

- Black powder coat only




4630-334CS
Switch End Cap

- End cap and switch (black powder coat only) for concealed switch option




4630-3179-1
On/Off Switch Assembly

- Black rocker switch, Plugs into high voltage PC board



4630-3179-2
Hold Open Switch Assembly

- Black rocker switch
- Field wired to low voltage PC board



4630-3180
PC Board Assembly

- High and low voltage PC boards connected to mounting bracket




4630-3454
Motor/Clutch Assembly

- A geared assembly in an LCN power operator that incorporates a "no destruct" feature



4630-3462
Control Box Assembly

- Digital controller with built-in 12/24 VDC power supply
- Programming and timing functions are adjusted on controller



4630-3498-2
AC Power Cable

- 2 wire cable to connect 120 VAC from PC board assembly to controller



4630-3498-1
Ribbon Cable Connector

- 16 wire ribbon cable connecting 1-24 pin terminal connectors to controller