



### 9400 Series

#### *Slim-line*

Works with rim exit devices with a 1/2" throw latchbolt

### 9500 Series

#### *Fire-Rated*

Works with rim exit devices with a 3/4" throw latchbolt

### 9600 Series

#### *Windstorm-Rated*

Works with rim exit devices with a 3/4" throw latchbolt

### 9700 Series

#### *Fire-Rated & Windstorm-Rated*

Works with Corbin Russwin SecureBolt™ and Yale SquareBolt® exit devices

*new*



# 9000 Family

## Surface Mounted Electric Strikes

### *Sophistication*

#### *Stylish Looks*

Designed with a stainless steel decorative cover

Available in six finishes to match any decor

Sleek lines complement ASSA ABLOY exit devices

### *Convenience*

#### *Easy Installation*

Completely surface mounted for quick installation

Base and cover are separate for easy adjustments

Field selectable fail safe/fail secure

### *Quality*

#### *Above and Beyond*

Exceeds Grade 1 standards for strength and performance

Components encased in 1/2" stainless steel housing

Independently verified above and beyond testing

ASSA ABLOY, the global leader in door opening solutions

[hesinnovations.com](http://hesinnovations.com)

# Series Options, Accessories & Specifications

## Optional Features

**LBM** » Latchbolt monitor

**LBSM** » Latchbolt  
strike monitor

## Accessories

**9400/9500/9600/9700-**

**108** » Spacer plate  
(black or 630 finish)

**9000-MTK** » Metal  
template kit

**SMB** » Surface  
mounting box

**2001M** » Plug-in  
bridge rectifier

**2004M** » Electrolynx  
adapter

**2005M3** » SMART Pac® III

**2006M** » Plug-in buzzer

## Frame Application

- Metal
- Wood

## Finishes

**630** » Satin stainless steel

**605** » Bright brass

**606** » Satin brass

**612** » Satin bronze

**613** » Bronze toned

**613E** » Dark oxidized  
satin bronze (NEW)

**629** » Bright stainless steel

## Electrical (continuous duty)

- .45 Amps @ 12 VDC
- .26 Amps @ 24VDC



## 9400 Series

### The Easy-Install, Slim-Line, Surface Mounted Solution

#### Standard Features

- Decorative cover for a sleek look
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Listings and Patents

- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- RoHS compliant
- Patents: 6,392,520 and 8,454,520

The 9400 Series works with rim exit devices with a 1/2" throw latchbolt



# 9500 Series

## The Strong & Durable, Fire-Rated, Surface Mounted Solution

### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

### Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- UL 1034, burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- California Fire Marshall listed
- NFPA 80-07 compliant
- RoHS compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520

The 9500 Series works with rim exit devices with a 3/4" throw latchbolt



# 9600 Series

## The Stylish, Windstorm-Rated, Surface Mounted Solution

### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

### Listings and Patents

- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,392,520 and 8,454,520

The 9600 Series works with rim exit devices with a 3/4" throw latchbolt



**hes**  
ASSA ABLOY

# 9700 Series

## Surface Mounted Electric Strike

Works with Corbin Russwin SecureBolt™ and  
Yale SquareBolt® exit devices

### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/  
fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal  
adjustability
- Five year limited warranty

### Listings and Patents

- UL 10C fire-rated, 3 hour (fail  
secure only)

- CAN4-S104 (ULC-S104), NFPA-  
252 and ASTM-E152 fire door  
conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- UL Listed to ANSI 250.13  
Severe windstorm listed
- Florida Building Code  
Approved (FL#14307)
- UL 1034 burglary-resistant  
listed and suitable for  
outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,390,520, 6,392,520  
and 8,454,520



Yale SquareBolt® Exit Device

For information call 800.626.7590 or visit us online  
at [www.hesinnovations.com](http://www.hesinnovations.com)

HES-056-0915