

# Strikes

## 1690 Concealed vertical rod device



**PB48**

Top strike for 1690 device.  
Packed with three 0.050"  
thick shims.  
1 1/16" x 1 1/16" x 7/16"  
(H x W x D)

## 1790 Rim device



**STK45**

Strike for inactive leaf,  
pair of doors with 1790  
device.  
3 1/4" x 1 5/16" x 1/4"  
(H x W x D)



**TD35**

Strike for single  
doors, 1790  
device. Includes  
1/8" shim.  
3" x 2" x 1/2"  
(H x W x D)

## (F) 19-R Rim devices



**F570**

Standard strike.  
2 5/8" x 1 1/4" x 13/16"  
(H x W x D)



**F490**

Optional strike.  
2 5/8" x 1 1/4" x 7/8"  
(H x W x D)



**565**

Adjustable surface  
mounted for use  
with blade or  
applied stops.  
Mounts flush for 1/2"  
stop height.



**571/571A**

Used on inactive  
leaf for device on  
active leaf of pair  
of doors without  
removable  
mullion. 571 keeps  
2 5/16" backset.  
571A is trimmer  
and projects less  
into opening.

## (F) 19-V Surface vertical rod devices



**3788**

Top strike for  
19-V.



**2130**

19-V bottom strike for  
grouting into concrete or  
masonry floors.




**4155**

19-V optional  
bottom strike.



**2126A**

19-V optional  
bottom strike.



**4215**

Angle bracket for 19-V  
devices flush transom  
applications. Does not  
require elimination of latch  
retention feature.



**Extension rods**

Extension rods are  
available in 12", 24"  
and 36" lengths in  
all finishes. Both  
ends tapped and  
all-thread included  
as connector.